

Vehicle Graphics

Care Guide

By following these cleaning and maintenance tips, you can ensure that your vehicle wrap maintains its premium appearance and longevity.

Improper or infrequent maintenance can lead to premature degradation of graphics and shorten the expected lifespan.

Cleaning Tips:

Hand Wash

1. **Pre rinse:** Using a hose, rinse the whole vehicle with clean water. This helps remove dirt particles and helps avoid scratching the graphics.
2. **Wash:** Use mild soapy water to gently wash the vehicle with a soft cloth or natural sponge. Work from the top of the vehicle down. Avoid unnecessary scrubbing.
3. **Rinse:** Rinse thoroughly with clean water.
4. **Dry:** Let the wrap dry naturally. To avoid water spotting, use a silicone squeegee to remove excess water, then finish drying with a micro-fiber or soft towel.

Note: Excess spraying at the wrong angle may cause failure points which result in the wrap lifting at the edges.

An automatic car wash that used brushes is not recommended, as the brushes may scratch the wrap or catch any edges and create a failure point.

Frequently Asked Questions:

What detergent should I use?

Use a mild car cleaning detergent and water mix that does not contain any strong soluble substances, alcohol, or abrasive components.

When should I clean my Vehicle?

You should not clean your vehicle within the first 48 hours of the wrap being applied.

Can I wax my vehicle?

Yes, as long as the wax does not contain petroleum distillates, which is found in many paste waxes. Products that are a combination of a waterless wash and wax are great options as long as the vehicle doesn't have a matte finish. Test the wax on an inconspicuous part of the vehicle first.

What about difficult spots?

Spot clean contaminants, such as bird droppings, bug splatter, etc. as soon as possible to avoid film damage. Start by soaking with hot soapy water, then rinse thoroughly. You can use isopropyl alcohol and a clean non-abrasive rag.

What if my wrap has a matte finish?

Use a waterless wash that is recommended for matte finishes. Do not use waterless products that contain wax as the wax may fill in the texture and cause shiny spots. Use a 50/50 mix of isopropyl alcohol and water to spot clean matte finish films.

